

BEOAMP 2

2 x 150W of audiophile sound quality



EFFICIENT AMPLIFIER FOR MULTIZONE INSTALLATIONS

The BeoAmp 2 amplifier is an ultra-compact and powerful audio power amplifier intended for single zone custom installation in modern homes, and can also be used in professional applications. BeoAmp 2 is designed for multiple placement options and fits a 1 unit space in a 19" rack installation as well as table and wall mount possibilities.



BANG & OLUFSEN



Front



Back

SPECIFICATIONS / FEATURES

Amplification	Placement options	Dimensions/Weight
Typical output power 100W per Ch., 8 Ω (1%THD+N, f=1kHz), @ 230Vac	Shelf (Feet included) 19 inch Rack (Rack ears included) Cabinet	Height 1.65 inches / 42 mm Width 7.87 inches / 200 mm Depth 9.84 inches / 250 mm Weight 1.9 kg
Peak power 150W per Ch., @ 8 Ω 300W per Ch., @ 4 Ω		
Connections	Standby power consumption	Power supply
Stereo RCA Line in Stereo RCA Loop out RJ45 Power Link input RJ45 Power Link loop out Phoenix speaker outputs Mains connector	Less than 0.5W	Universal Mains 85-264 Vac, 45-65 Hz
Power Management	Thermal dissipation	Colours
Audio input sense, 12V trigger and PowerLink	Passive cooling	Black cabinet

FEATURES	<ul style="list-style-type: none">Ultra-compact enclosure (2 pcs BeoAmp 2 fits in a 1U rack)Extremely low weight - up to seven times lighter than similar productsUp to 2 x 150W channels of audiophile sound qualityVery low power consumption and heat dissipation thanks to efficient ICEpower Class-D technologyComprehensive protection keeps the music playing and your quality costs downRemovable rack ears and feet are included in the product packaging
-----------------	---